



MATERIAL : BODY-BRASS  
 SLEEVE-BRASS  
 CONTACT-BRASS  
 INSULATOR-TEFLON  
 C WASHER-SUS304  
 SI RUBBER-SILICONE  
 SHELL-BRASS  
 CAP-BRASS  
 RING-BRASS

FINISH : BODY-NICKEL PLATING  
 SLEEVE-NICKEL PLATING  
 CONTACT-GOLD PLATING OVER NICKEL  
 SHELL-NICKEL PLATING  
 CAP-NICKEL PLATING  
 RING-NICKEL PLATING

圖號	不同之處
806-110201	BODY(有階層)、SHELL、SLEEVE、SUS303、RING、CAP不同 RD316
806-110202	BODY(有階層)、SHELL、SLEEVE、SUS303、RING、CAP不同 TGG
806-110203	同 806-1102 設計、TGG
806-110204	同 806-110202 設計、TGN
806-110205	BODY(有階層)、SLEEVE、RING 不同 TGG
806-110206	設計不同 TGA

DIMENSIONS ARE IN MILLIMETERS TOLERANCE				C&C ELECTRONICS CONNECTORS INC	
· ×	±0.5	ANGLE ±3°	SCALE	5:1	
· × ×	±0.1		REV	A-2	
· × × ×	±0.05				
DRAWN 崔振烽		DATE 94.01.24		TITLE SMA R/A PLUG CRIMP FOR RG <sub>316</sub> <sup>174</sup> u	
APPROVAL		DATE		DRAWING NO 806-1102	
				FILE NO 806-0014	