



Impedance: 50ohm  
 Frequency Range: 0~6.0 GHZ  
 VSWR: 1.35 MAX  
 Dielectric withstanding Voltage:  
     500 volts rms max  
 Insulation Resistance:  
     1000 meg ohm min

MATERIAL : BODY-BECU  
           SLEEVE-BRASS  
           INSULATOR-PP  
           CONTACT-BRASS  
           INSULATOR-TEFLON  
           CAP-BRASS  
           FURRULE-BRASS  
 FINISH : BODY-GOLD PLATING OVER NICKEL  
           SLEEVE-GOLD PLATING OVER NICKEL  
           CONTACT-GOLD PLATING OVER NICKEL  
           CAP-GOLD PLATING OVER NICKEL  
           FURRULE-GOLD PLATING OVER NICKEL

DIMENSIONS ARE IN MILLIMETERS				C&C ELECTRONICS CONNECTORS INC	
TOLERANCE				TITLE	
· × ±0.5	ANGLE ±3°	SCALE 8:1		MCX R/A MALE CRIMP FOR RG 174U 316U	
· × × ±0.1		REV A-1		DRAWING NO 802-1105	
· × × × ±0.05		DRAWN 郭姿良		DATE 90.09.13	
APPROVAL		DATE		FILE NO 802-0011	