



Impedance: 50ohm
 Frequency Range: 0~12.4GHz
 Temperature Range: -60°C~160°C
 Insulation Resistance: 5000 megohms min
 Return Loss: -24dB ~ -32dB
 VSWR: 1:1.1

MATERIAL : BODY-BRASS
 INSULATOR-TEFLON
 SLEEVE-BRASS
 CONTACT PIN-BRASS
 FERRULE-BRASS
 C WASHER-SUS 304
 SI RUBBER-SILICONE
 SHELL-BRASS
FINISH : BODY-NICKEL PLATING
 SLEEVE-NICKEL PLATING
 CONTACT PIN-GOLD PLATING OVER NICKEL
 FERRULE-NICKEL PLATING
 SHELL-NICKEL PLATING

圖號	不同之處
806-112801	同806-1128 設計 (TGG)

DIMENSIONS ARE IN MILLIMETERS				C&C ELECTRONICS CONNECTORS INC	
TOLERANCE				TITLE SMA STRAIGHT MALE CRIMP FOR LMR240	
·× ±0.5	ANGLE ±3°	SCALE	5:1	DRAWING NO 806-1128	
·×× ±0.1		REV	A-0	FILE NO 806-0094	
·××× ±0.05		DRAWN	郭姿良	DATE	92.07.25
APPROVAL		DATE			