



1. INTERFACE PER MIL-STD-348
2. COUPLING NUT RETENTION: 15 INCH*LBS
3. COUPLING NUT RETENTION: 60 LBS AXIAL
4. CONTACT RETENTION: 6 LBS AXIAL
5. INSULATOR RETENTION: 6 LBS AXIAL
6. DUREBILITY: TEST AFLER 100 CYCLES

9	RING	BRASS	1	GOLD
8	CAP	BRASS	1	GOLD
7	SI RUBBER	SILICONE	1	
6	C WASHER	SUS304	1	
5	SHELL	BRASS	1	GOLD
4	CONTACT	BRASS	1	GOLD
3	INSULATOR	TEFLON	1	
2	SLEEVE	BRASS	1	GOLD
1	BODY	BRASS	1	GOLD
NO	DESCRIPTION	MATERIAL	Q' TY	FINISH

DIMENSIONS ARE IN MILLIMETERS
TOLERANCE

· × ±0.5
· × × ±0.1
· × × × ±0.05

ANGLE ±3°

SCALE 5:1

REV A-1

DRAWN 潘曉臨

DATE 100.04.09

APPROVAL

DATE

C&C ELECTRONICS CONNECTORS INC

TITLE SMA MALE R/A FOR RD316u

DRAWING NO 806-1140

FILE NO 806-0119