



IMPEDANCE:50 OHM  
 FREQUENCY RANGE:0 TO 2.5 GHZ  
 VSWR:1.25 MAX  
 VOLTAGE RATING:355 VOLTS RMS MAX  
 DIELECTRIC WITSTANDING VOLTAGE:1,000 VOLTS RMS MAX  
 INSULATION RESISTANCE:5,000 MEGOHMS MIN(TEFLON)

**MATERIAL :** BODY-BRASS  
 CONTACT-BRASS  
 SHELL-BRASS  
 INSULATOR-TEFLON  
 FURRULE-BRASS  
**FINISH :** BODY-NICKEL PLATING  
 SHELL-NICKEL PLATING  
 FURRULE-NICKEL PLATING  
 CONTACT-GOLD PLATING OVER NICKEL

DIMENSIONS ARE IN MILLIMETERS TOLERANCE				C&C ELECTRONICS CONNECTORS INC	
·×	±0.5	ANGLE ±3°	SCALE	5:1	
·××	±0.1		REV	A-4	
·×××	±0.05				
DRAWN 潘曉臨		DATE		98.11.20	
APPROVAL		DATE			
				TITLE	
				MINI UHF MALE CONNECTOR	
				DRAWING NO	
				830-1113	
				FILE NO	
				830-0035	