



IMPEDANCE: 50 OHM  
 FREQUENCY RANGE: 0 TO 6.0 GHz  
 VSWR: 0-4GHz=1.2MAX(STRIGHTHT)  
 1.25MAX(RIGHT ANGLE)  
 4-6GHz=1.25MAX(ATRAINGT)  
 1.4MAX(RAIGHT ANGLE)  
 INSULATION RESISTANCE: 1.000 MEGOHMS MIN

MATERIAL : BODY-BRASS  
 SLEEVE-BRASS  
 INSULATOR-TEFLON  
 CONTACT-BRASS  
 C WASHER-BERYLLIUM COPPER  
 FURRULE-BRASS  
 CAP-BRASS

FINISH : BODY-GOLD PLATING OVER NICKEL  
 SLEEVE-GOLD PLATING OVER NICKEL  
 CONTACT-GOLD PLATING OVER NICKEL  
 C WASHER-GOLD PLATING OVER NICKEL  
 FURRULE-GOLD PLATING OVER NICKEL  
 CAP-GOLD PLATING OVER NICKEL

DIMENSIONS ARE IN MILLIMETERS  
 TOLERANCE

C&C ELECTRONICS CONNECTORS INC

|          |       |           |            |
|----------|-------|-----------|------------|
| · ×      | ±0.5  | ANGLE ±3° | SCALE 10:1 |
| · × ×    | ±0.1  |           |            |
| · × × ×  | ±0.05 | REV       | A-0        |
| DRAWN    | 郭姿良   | DATE      | 90.09.11   |
| APPROVAL |       | DATE      |            |

|            |                           |
|------------|---------------------------|
| TITLE      | MMCX MALE R/A FOR RG 174u |
| DRAWING NO | 800-1106                  |
| FILE NO    | 800-0018                  |